

PATENT ABSTRACTS OF JAPAN

(11)Publication number:

2000-146031

(43)Date of publication of application: 26.05.2000

(51)Int.CI.

F16L 11/04 B32B 1/08

(21)Application number: 10-320187

(71)Applicant: TOKAI RUBBER IND LTD

(22)Date of filing:

11.11.1998 (72

(72)Inventor: FURUTA NORIHIKO


NIKI NOBUAKI


(54) NONTRANSPARENT TYPE COMPOUND HOSE

(57)Abstract:

PROBLEM TO BE SOLVED: To prevent damage and breakage of metal foil according to bending or the like of a hose, by using a laminate sheet, with a resin film layered to the metal foil and a reinforcement of large elongation resistance, to form a laminate layer, in the nontransparent type compound hose having the laminate layer including the metal foil.

SOLUTION: This nontransparent type compound hose 6 has a double layer structure successively providing from the innermost layer a IIR (butyl rubber)— made rubber inner tube 1, laminate layer 2, IIR—made elastic material layer 3, reinforcing layer 4 formed by blade winding a reinforcing thread, and an EPDM—made rubber outer tube 5. In that hose 6, the laminate layer 2 is formed by using a laminate sheet 11 fixing metal foil 9 of aluminum or the like and a canvas—made reinforcement 10 in sandwich shape between resin film layers 7, 8 of thin film formed by a thermoplastic resin of PET or the like. The metal foil 9 is bonded to the reinforcement 10 by a





bonding agent, so as to prevent damage and breakage of the metal foil 9 due to acting of tensile force in the laminate layer 2.

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

BEST AVAILABLE COPY